



# NEOFLEX™ PREMIUM GYM TILES

SKU: NEOFLEX-PGT





## PRODUCT DESCRIPTION

These 15 mm x 1m x 1m rubber tiles are easily installed and are a cost effective choice for a very tough, sound deadening, anti-vibration and comfortable tile surface is preferred. For an indoor setting, you can loose lay them or bond them down using the 4 x Stikibak tabs provided on the back. These tiles are used for the official competition floor of some of Europe's largest CrossFit events like The German Throwdown.

Installation not provided.

### Specs:

| Property                 | Standard       | Result               |
|--------------------------|----------------|----------------------|
| Thickness                |                | 15 mm                |
| Dimensions               |                | 1010 mm x 1010 mm    |
| Weight                   |                | 15.0 kgs             |
| Shore Hardness A         |                | 60º                  |
| Resilience               | ASTM D 2240    | 40%                  |
| Tear Strength Top Layer  | ASTM D 624     | 1.55 MPa (± 225 psi) |
| Tear Strength Base layer | ASTM D 624     | 0.70 MPa (± 101 psi) |
| Taber Abrasion           | ASTM C 504     | 0.66 gr              |
| Remaining Indentation    | DIN 53960      | 0.05 mm              |
| Flammability             | EN 13501-1     | Class Cfl-s1         |
|                          | ASTM E648      | Class I [4.4 kW/m2]  |
| Coefficient of Friction  | ASTM D 2047-97 | Dry: 1.03 Wet: 0.97  |

## ADDITIONAL INFORMATION

### More Information

#### Product Dimension

101 x 101cm

#### Warranty

6 months