




# NEOFLEX HIGH IMPACT GYM TILES

SKU: NEOFLEX-HPT





PRODUCT  
DESCRIPTION

Each piece is 50 x 50 x 5cm in size.




## Feel the Difference.

Neoflex™ Jazz 500 High Impact Tiles are 20 - 100 mm thick, robust, resilient rubber tiles installed in free weight areas and designed to attenuate the impact of heavy free weights that thinner surfaces cannot achieve.

Neoflex™ Jazz 500 High Impact Tiles provide superior sound and vibration insulation ensuring that areas below, around and above the gym remain quiet.

Supplied with a dense synthetic EPDM rubber top layer in flecked colors, and supported by a recycled rubber base layer, Neoflex™ Jazz 500 High Impact Tiles achieve a Cfl-s1 Flammability and Smoke Developed Rating according to EN 13501-1. Logos, agility & functional zone markings can be in-laid in the surface as well.



Property	Standard	Result
Thickness		20 - 100 mm
Size		505 mm x 505 mm 605 mm x 605 mm 1010 mm x 1010 mm
Shore Hardness	ASTM D 2240	60°
Resilience	DIN 18032-2	40%
Tear Strength Top Layer	ASTM D 624	1.25 MPa
Tear Strength Base Layer	ASTM D 624	0.70 MPa
Taber Abrasion	ASTM C 504	0.66 gr
Remaining Indentation	DIN 53960	0.05 mm
Flammability	EN 13501-1	C <sub>f</sub> -s1
Coefficient of Friction	ASTM D 2047-97	Dry: 1.03 Wet: 0.97



ADDITIONAL  
INFORMATION

### More Information

**Product Dimension**

50 x 50 x 5cm

**Warranty**

6 months